

# MOLL-MOTOR

Silniki o sprawności premium IE3 3000 obr/min, S1, IP55, klasa iz. F  
temp. pracy -20°C do +40°C, klimat umiarkowany, RAL7020 mat.

PN-EN 60034-1



typ silnika	ilość bieg.	obroty (obr/min)	moc (kW)	prąd znam. (A)	sprawność $\eta$	współ. mocy $\cos\varphi$	moment (Nm)	Ms/Mn	Is/In	Mb/Mn	bezwładność	hałas Lw	waga
											kgm2	dB(A)	(kg)
Y2PE-132S2-2	2	2940	7,5	13,7	90,1	0,88	24,4	2,0	7,9	2,3	0,01643	79	65
Y2PE-160M1-2	2	2950	11	19,6	91,2	0,89	35,6	2,0	8,1	2,3	0,05398	81	113
Y2PE-160M2-2	2	2950	15	26,5	91,9	0,89	48,6	2,0	8,1	2,3	0,06176	81	124
Y2PE-160L-2	2	2950	18,5	32,5	92,4	0,89	59,9	2,0	8,2	2,3	0,07161	81	141
Y2PE-180M-2	2	2960	22	38,5	92,7	0,89	71,0	2,0	8,2	2,3	0,08924	83	177
Y2PE-200L1-2	2	2970	30	52,1	93,3	0,89	96,5	2,0	7,6	2,3	0,18002	84	224
Y2PE-200L2-2	2	2970	37	64,0	93,7	0,89	119	2,0	7,6	2,3	0,18998	84	240
Y2PE-225M-2	2	2970	45	76,8	94,0	0,90	145	2,0	7,7	2,3	0,33354	86	337
Y2PE-250M-2	2	2980	55	93,5	94,3	0,90	176	2,0	7,7	2,3	0,46384	89	391
Y2PE-280S-2	2	2980	75	127,0	94,7	0,90	240	1,8	7,1	2,3	1,08887	91	518
Y2PE-280M-2	2	2980	90	152,0	95,0	0,90	288	1,8	7,1	2,3	1,14866	91	550
Y2PE-315S-2	2	2980	110	185,0	95,2	0,90	353	1,8	7,1	2,3	1,49522	92	940
Y2PE-315M-2	2	2980	132	224,0	94,5	0,90	423	1,8	7,1	2,3	2,11070	92	985
Y2PE-315L1-2	2	2980	160	265,0	95,6	0,91	513	1,8	7,2	2,3	2,39391	92	1100
Y2PE-315L2-2	2	2980	200	331,0	95,8	0,91	641	1,8	7,2	2,2	2,65370	92	1200
Y2PE-355M-2	2	2980	250	414,0	95,8	0,91	801	1,6	7,2	2,2	3,34500	100	1725
Y2PE-355L-2	2	2980	315	522,0	95,8	0,91	1009	1,6	7,2	2,2	3,90250	100	1930

Zastrzegamy możliwość zmian technicznych

